## CARATTERISTICHE TECNICHE / TECHNICAL DATA
## CARACTÉRISTIQUES TECHNIQUES / TECHNISCHE DATEN

| MOD. | | | | | | |
|---|---|---|---|---|---|---|
| **NEW EUROSFILO** | | | | | | |
| 14 \| 2 \| 9 HQ | 14 m | 9m | 200kg | CONT | IN SHAPE | 90°+90° |
| 15 \| 2 \| 10 HQ JIB | 15m | 10m | 200kg | CONT | - | 90°+90° |
| 17 \| 2 \| 8,5 HQ | 17m | 8,5m | 200kg | CONT | IN SHAPE | 90°+90° |
| 17 \| 2 \| 11 HQ | 17m | 11m | 200kg | CONT | - | 90°+90° |
| 17 \| 2 \| 12 HQ | 17m | 12m | 250kg | CONT | - | 90°+90° |
| 19 \| 2 \| 8,5 HQ | 19m | 8,5m | 200kg | CONT | IN SHAPE | 90°+90° |
| 19 \| 2 \| 11 HQ | 19m | 11m | 200kg | CONT | - | 90°+90° |
| 19 \| 2 \| 14 HQ | 19m | 14m | 250kg | CONT | - | 90°+90° |
| 20 \| 2 \| 11 HQ | 20m | 11m | 200kg | CONT | - | 90°+90° |
| 20 \| 2 \| 11 HQ JIB | 20m | 11m | 230kg | CONT | - | 90°+90° |
| 22 \| 2 \| 14 HQ | 22m | 14m | 250kg | CONT | - | 90°+90° |
| 22 \| 2 \| 14 HQ JIB | 22m | 14m | 250kg | CONT | - | 90°+90° |
| 24 \| 2 \| 11 HQ 4S | 24m | 11m | 230kg | CONT | - | 90°+90° |
| 24 \| 2 \| 14 HQ JIB | 24m | 14m | 250kg | CONT | - | 90°+90° |
| **NEW EUROSKY** | | | | | | |
| 14 \| 2 \| 6 HD JIB | 14m | 6m | 200kg | CONT | A+A | 90°+90° |
| 16 \| 2 \| 7,5 HQ JIB | 16m | 7,5m | 200kg | CONT | A+A | 90°+90° |
| 18 \| 2 \| 7,5 HQ | 18m | 7,5m | 200kg | CONT | IN SHAPE | 90°+90° |
| 18 \| 2 \| 7,5 HQ | 18m | 7,5m | 260kg | CONT | IN SHAPE | 90°+90° |
| 20 \| 2 \| 10 HQ JIB | 20m | 10m | 200kg | CONT | - | 90°+90° |
| 21 \| 2 \| 9 HQ | 21m | 9m | 200kg | CONT | - | 90°+90° |
| 21 \| 2 \| 9 HQ | 21m | 9m | 260kg | CONT | IN SHAPE | 90°+90° |
| 22 \| 2 \| 10 HQ JIB | 22m | 10m | 200kg | CONT | - | 90°+90° |
| **NEW EUROSKY - HEAVY DUTY** | | | | | | |
| 26 \| 2 \| 13 HQ JIB | 26m | 13m | 250kg | CONT | - | 90°+90° |
| 28 \| 2 \| 14 HQ | 28m | 14m | 250kg | CONT | - | 90°+90° |
| 31 \| 2 \|17 HQ JIB | 31m | 17m | 250kg | CONT | - | 90°+90° |
| 33 \| 2 \| 18 HQ JIB | 33m | 18m | 250kg | CONT | - | 90°+90° |
| **TRUCK MOUNTED** | | | | | | |
| 45 \| 2 \| 20 HD JIB | 45m | 20m | 250kg | CONT | - | 90°+90° |
| **VAN MOUNTED** | | | | | | |
| HVM 12 | 12m | 6,5m | 120kg | 360° | NO OUTRIGGERS | FIXE |
| HVM 14 | 14m | 7,2m | 200kg | 360° | N.2 OUTRIGGERS | FIXE |
| **MINI TRUCKS** | | | | | | |
| 14 \| 2 \| 6 HD JIB | 14m | 6m | 200kg | CONT | - | 90°+90° |
| 16 \| 2 \| 7,5 HQ JIB | 16m | 7,5m | 200kg | CONT | - | 90°+90° |
| **TRACTOR** | | | | | | |
| XTRACTOR 12 | 12m | 4,5m | 200kg | 180° | - | FIXE |
| XTRAILER 12 | 12m | 4,5m | 200kg | CONT | - | FIXE |
| XTRAILER 14 | 14m | 6,2m | 200kg | CONT | - | FIXE |
| **PC SELF SOLUTION** | | | | | | |
| X4 12 | 12m | 4,5m | 150kg | CONT | - | FIXE |
| X4 14 | 14m | 6,2m | 120kg | CONT | - | FIXE |
| 14 \| 2 \| 7,6 HQ JIB | 14m | 7,6m | 250kg | CONT | - | 90°+90° |
| 14 \| 2 \| 6 HD JIB | 14m | 6m | 200kg | CONT | - | 90°+90° |
| 16 \| 2 \| 7,5 HQ JIB | 16m | 7,5m | 200kg | CONT | - | 90°+90° |

| MOD. | | | | | | |
|---|---|---|---|---|---|---|
| **INSULATED - EUROSKY - I** | | | | | | |
| 16 \| 2 \| 11 46KV - CAT.C | 16m | 11m | 270kg | CONT | - | 90°+90° |
| 18 \| 2 \| 12 60-115KV - CAT.B | 18m | 12m | 270kg | CONT | | 90°+90° |
| 19 \| 2 \| 13 46KV - CAT.C | 19m | 13m | 270kg | CONT | | 90°+90° |
| 21 \| 2 \| 14 46KV - CAT.C | 21m | 14m | 250kg | CONT | | 90°+90° |
| **SOLAR** | | | | | | |
| SOLAR 11 | 11m | 4m | 400kg | - | - | 90°+90° |
| **LEOPARD** | | | | | | |
| LEOPARD 14 | 14m | 6,5m | 200kg | 360° | - | 90°+90° |
| LEOPARD 17 | 17m | 7,5m | 250kg | 400° | - | 90°+90° |
| LEOPARD 21 | 21m | 9m | 200kg | 400° | - | 90°+90° |
| LEOPARD 25 | 25m | 11,5m | 250kg | 400° | - | 90°+90° |
| **FIRE-FIGHTING** | | | | | | |
| EUROFLAG 45/22/4 HQ | 44m | 24m | 500kg | 360° | - | 90°+90° |
| **ELECTRIC RANGE** | | | | | | |
| XMINI 12 | 12m | 4,5m | 200kg | 360° | - | 90°+90° |
| XMINI 14 | 14m | 6,2m | 200kg | 360° | - | 90°+90° |
| XTRAILER 12 - BATTERIES | 12m | 4,5m | 200kg | CONT | - | 90°+90° |
| XTRAILER 14 - BATTERIES | 14m | 6,2m | 200kg | CONT | - | 90°+90° |
| LEOPARD 17 - LITHIUM BATTERY | 17m | 7,5m | 200kg | 400° | - | 90°+90° |
| LEOPARD 21 - LITHIUM BATTERY | 21m | 9m | 200kg | 400° | - | 90°+90° |
| LEOPARD 25 - LITHIUM BATTERY | 25m | 11,5m | 200kg | 400° | - | 90°+90° |

- Altezza di lavoro
- Working height
- Hauteur de travail
- Arbeitshöhe

- Sbraccio laterale
- Maximum outreach
- Déport latéral
- Seitliche Reichweite

- Stabilizzatori sempre in sagoma per garantire massima sicurezza e velocità di piazzamento
- In shape outriggers to assure highest safety and easiest placing
- Béquilles en gabarit qui assurent toute sécurité et un placement très facile
- Abstützungen innerhalb der Fahrzeugkontur, um maximale Sicherheit und eine rasche Positionierung zu gewährleisten

- Portata in navicella (max. 2 persone)
- Basket's working load (max 2 persons)
- Charge utile dans le panier (max. 2 personnes)
- Tragkraft des Hebekorbs (max. 2 Personen)

- Rotazione Torretta
- Turret Rotation
- Rotation tourelle
- Drehung des Turms
  360° - 360°Continuous - 400° - 180°

- Rotazione idraulica della navicella
- Rotating basket hydraulically operated
- Rotation de la nacelle à fonctionnement hydraulique
- Hydraulische Korbdrehung


- Disponibile versione ecologica con olio biodegradabile
- Now available ecological model with biodegradable oil
- Maintenant disponible version écologique avec huile biodégradable
- Auch in der Öko-Version mit biologisch abbaubarem Öl erhältlich

- Sicurezza al 100%
- 100% safe
- Sécurité au 100%
- 100% Sicherheit


COMET OFFICINE
Head Office - Show Room - Factory:
Via Castelfranco, 46 - Località Tivoli - 40017 San Giovanni in Persiceto (BO) ITALY
Phone +39.051.6878711 - Fax +39.051.799902
Email: info@officinecomet.com - Website: www.officinecomet.com



# INSULATED

### 16 | 2 | 11 HQ ANSI 46/69 KV CAT. C





Min. GVW 9 Ton
All available with in shape outriggers H type

### 18 | 2 | 12 HQ ANSI 69/115 KV CAT. B




Min. GVW 11 Ton
All available with in shape outriggers H type

### 19 | 2 | 13 HQ ANSI 46/69 KV CAT. C




Min. GVW 11 Ton

# INSULATED
## DIN VDE


### 1 KV BASKET AND TRUCK FROM 14 TO 22



Min. GVW 3.5 Ton

# INSULATED

### 21 | 2 | 14 HQ ANSI 46/69 KV CAT. C





Min. GVW 11 Ton

# SOLAR



TRUCK MIN GVW 3.5 TON




# LEOPARD

### 100% HYDRAULIC 14





### ELECTRO-HYDRAULIC 17|21|25

Lithium Battery Version Available




# EUROFLAG


### FIRE FIGHTING PURPOSE






# ELECTRIC RANGE

XMINI 12




XMINI 14






XTRAILER 12 - BATTERIES
XTRAILER 14 - BATTERIES



LEOPARD 17 - LITHIUM BATTERY
LEOPARD 21 - LITHIUM BATTERY
LEOPARD 25 - LITHIUM BATTERY






Since 1960
COMET OFFICINE

SALI CON NOI
CLIMB WITH US
MONTE AVEC NOUS
STEIGEN SIE MIT UNS AUF





Tecnologia e sicurezza per lavorare in quota
Safety and technology for aerial works
Technologie et sécurité pour travaux aériens
Technologie und Sicherheit bei der Arbeit in der Höhe

100% MADE IN ITALY · ECO · 100% SAFE · CE · BUREAU VERITAS Certification

## NEW EUROSFILO

**14 | 2 | 9 HQ**







Min. GVW 3.5 Ton

**15 | 2 | 10 HQ JIB**







Min. GVW 3.5 Ton

**17 | 2 | 8.5 HQ**
**17 | 2 | 11 HQ**
**17 | 2 | 12 HQ**







Min. GVW 3.5 Ton

Lateral outreach depending on truck GVW

**19 | 2 | 8.5 HQ**
**19 | 2 | 11 HQ**
**19 | 2 | 14 HQ**






Min. GVW 3.5 Ton


**All available with in shape outriggers H type**

Lateral outreach depending on truck GVW

## NEW EUROSFILO

**20 | 2 | 11 HQ**
**20 | 2 | 11 HQ JIB**







Min. GVW 6 Ton

**22 | 2 | 14 HQ**
**22 | 2 | 14 HQ JIB**







Min. GVW 6 Ton

**24 | 2 | 11 HQ 4S**
**24 | 2 | 14 HQ JIB**






Min. GVW 6 Ton

## NEW EUROSKY

**14 | 2 | 6 HQ JIB**







Min. GVW 3.5 Ton

**16 | 2 | 6 (7.5) HQ JIB**







Min. GVW 3.5 Ton

**18 | 2 | 6.5 (7.5) HQ**
**18 | 2 | 7.5 HQ**







Min. GVW 3.5 Ton

**21 | 2 | 9 HQ**
**21 | 2 | 7 (9) HQ**






Min. GVW 3.5 Ton

## NEW EUROSKY

**22 | 2 | 10 HQ JIB**







Min. GVW 3.5 Ton

## NEW EUROSKY HEAVY DUTY

**26 | 2 | 13 HQ JIB**







Min. GVW 6 Ton

**28 | 2 | 14 HQ**







Min. GVW 6 Ton

## NEW EUROSKY

**HEAVY DUTY**

**31 | 2 | 17 HQ JIB**







Min. GVW 7 Ton

**33 | 2 | 16(18) HQ JIB**







## EUROSKY-T

**45 | 2 | 20 T**







Min. GVW 26 Ton


## VAN MOUNTED

**HVM 12 | 2 | 6.5 JIB VAN**
**HVM 14 | 2 | 7.2 JIB VAN**

Min. PTT 3.5 Ton







## MINITRUCKS

**14 | 2 | 6 HQ JIB**






Min. GVW 2.2 Ton

**16 | 2 | 7.5 HQ JIB**






Min. GVW 2.2 Ton

## PICK - UP SOLUTIONS

**X4**











Min. GVW 2.8 Ton

**NEW EUROSKY**

**14 | 2 | 6.4 (7.4) HQ JIB**

KING CAB & SUPER CAB & SINGLE CAB VEHICLE






**14 | 2 | 6 HQ JIB**
**16 | 2 | 6 (7.5) HQ JIB**

SINGLE CAB VEHICLE






## X RANGE

**X TRACTOR**






Weight 1,650 kg

**X TRAILER**